

NEW

KSTAR

3-Ph BluE Residential ESS

All In One Energy Storage System
CATL Battery Solutions

Coming soon 2022 Q3



CATL LFP Battery, Stable and safe
Module, pack, system, triple protection



Adjustable power in each phase
Support diesel generator control(DI/DO)



Modular design, Plug and play
Mobile APP Monitoring



Supporting 200% oversized PV power
On&OFF Grid parallel system

Battery Model		BluE-PACK5.1	
Physical		Operation	
Battery type	LFP (LiFePO4)	Max. Charge/Discharge Current	50A/80A
System Weight	54KG	Rated DC power	4096W
Dimension (W x H x D)	540*490*240	Max. Charge/Discharge Power	2825W/4096W
IP Protection	IP65	Operating Temperature Range	0 to 50°C charging -10 to 50°C discharging
Warranty	5 Year Product Warranty, 10 Year Performance Warranty	Humidity	0~95% (No condensation)
Electrical		BMS	
Energy Capacity	5.12kwh	Capacity	100-400Ah
Usable Capacity	4.6kwh	Power Consumption	<2W
Depth of Discharge (DoD)	90%	Communication	CAN & RS485
Rated Voltage	51.2V	Monitoring Parameters	System voltage, current, cell voltage, cell temperature, PCBA temperature measurement
Operating Voltage Range	44.8-56.5V	Certificate	
Internal Resistance	<20mΩ	Safety(Cell)	
Cycle Life	10000cycle	Pack: IEC/EN 62619;UN38.3 Cell: IEC/EN 62619;UN38.3;UL1973	

Hybrid Inverter Model	BluE-S 10KT
PV String Input	
Max. Continuous PV Input Power	20kW
Max. DC Voltage	1100V
Nominal Voltage	720V
MPPT Voltage Range	140V-1000V
MPPT Range (Full Load)	420V-850V
Start Voltage	130V
MPPT Tracker / Strings	2/2
Max. Input Current Per MPPT	15A
Max. Short-circuit Current Per MPPT	20A
AC Output (Grid)	
Nominal AC Output Power	10kW
Max. AC Apparent Power	11kVA
Nominal AC Voltage	400Vac 3W+N+PE
AC Grid Frequency Range	50 / 60Hz
Max. Output Current	14.5A
Max. Input Current	16A
Power Factor (cosΦ)	0.8leading-0.8lagging *
Battery Input	
Battery Type	LFP (LiFePO4)
Nominal Battery Voltage	48V
Charging Voltage Range	40-60V
Max. Charging Current	200A
Max. Discharging Current	200A
AC Output (Backup)	
Max. Output Apparent Power	10kVA
Rated Output Power	9.2kW
Rated/Max. Output Current	14.5A/16A
Nominal Output Voltage	400V
Nominal Output Frequency	50/60Hz (±2%)
Output THDv (@Linear Load)	<3% (Linear Load)
Protection	
Anti-islanding Protection	Yes
Output Over Current	Yes
DC Reverse Polarity Protection	Yes
String Fault Detection	Yes
AC/DC Surge Protection	DC Type II;AC Type III
Insulation Detection	Yes
AC Short Circuit Protection	Yes
General Specifications	
Dimensions W x H x D	540*980*240mm
Weight	42kg
Operating Temperature Range	-25°C~+60°C (Derating > 45°C)
Noise (dB)	<25
Cooling Type	Natural Convection
Max. Operation Altitude	3000m (Derating > 2000m)
Operation Humidity	0~95% (No Condensation)
IP Class	IP65
Topology	Battery Isolation
Communication	RS485/CAN2.0/WIFI/4G
Display	LCD/APP

* 0.95leading-0.95lagging for Germany

KSTAR

Stock code: 002518

Add: 4/F, No.1 Bldg. Software Park, Keji C. Rd. 2nd, Hi-Tech Industrial Zone, Shenzhen 518057, P.R.China

Website: www.kstar.com E-mail: sales@kstar.com